INTRODUCING THE

NEW FERRIS Z1-P

ENGINEERED TO OWN THE JOB.



FERRIS®

Z1-P STAND-ON SERIES

ENGINEERED TO OWN THE JOB

The all-new Ferris Z1-P platform redefines what a compact stand-on mower can be. It is built for the professional landscaper who demands agility, productivity and comfort. The ground-up design provides easy serviceability and maintenance access.



TRIPLE™ MOWING TECHNOLOGY

The new Z1-P platform comes standard with our patended Triple™ mower decks. To compliment the range further, a 81 cm deck has been added to the line up to allow for access to even the most narrow entrances.



NEW DASHBOARD LAYOUT

Enjoy effortless operation with our redesigned, easy-access dashboard, paired with automatic PTO shutdown that instantly stops the blades when you step off the platform. This allows you to safely clear obstacles and quickly resume mowing without restarting the engine.



SPEED SELECTOR

The new, one-hand adjustable, speed control selector makes it easier to change between the three maximum speed settings.



UPGRADED OPERATOR PLATFORM

To provide a secure stance we've widened the operator platform and added cleated footrests. Combined with the suspended platform featuring tunable dampening, our Z1-P stand-on mowers offer superior comfort all day long.

DESIGNED FROM THE GROUND UP

The Z1-P stand-on mower platform has been designed from the ground up:

- Versatility: The new Z1-P stand-on mowers are fitted with our patented Triple™ mower decks; heavy-duty, configurable decks that can handle daily commercial use. All parts to convert from rear to side discharge, or mulching, are included in the box. With deck sizes ranging from the nimble 81 cm to the high-demand 122 cm, there is a Z1-P configuration for every landscaper.
- Extended Warranty: We've extended our protection from 500 to 750 hours or 4 years, whichever comes first. During the first 2 years you can enjoy unlimited hours. We're betting on this machine so you don't have to.
- Serviceability: We've simplified the service touchpoints, made the transaxles easily accessible, and reduced overall complexity. It's cleaner, faster, and cheaper to own over the life of the machine. Less time in the shop means more time on the grass.
- Comfort: The simplified operator platform offers more space to stand and features additional footrests on the side that provide a sturdy stance when mowing an incline. Tunable dampening offers a smooth ride. The dashboard has been redesigned, providing a clear view of all the controls and easier access. The speed selector can now be changed with one hand.
- Power & Productivity: The Z1-P platform offers a compact footprint similar to its predecessor, allowing transport in the back of most standard-sized vans in Europe. Powerful Kawasaki engines combined with commercial Hydro-Gear® transaxles enable you to be productive, hitting ground speeds of up to 12,8 km/h.

AVAILABLE ACCESSORIES

- Service Jack Kit
- LED Light Kit
- Cup holder (included with PX models)

VIBRATION*

HAV <2,5 m/s²

UP TO

0,73 (81 CM)	0,93 (91 CM)	1,25 (122 CM)

HECTARES / HOUR
BASED ON 80% EFFICIENCY

TRIPLE MOWING TECHNOLOGY

All discharge options you will ever need! The Triple™ mower deck hosts multiple mowing configurations in a single deck design that can be converted as required. With this "all-in-one" mower deck approach Ferris is addressing the changing needs of our customers.

Traditional mowing methods, regional preferences, climate differences as well as changing seasons and grass varieties; they all require different cutting and discharging methods. The Triple™ mowing system eliminates stress of choice for the mower owner. No matter the circumstances, the best mower configuration is always at your disposal.

* Declared vibration emission value per iso 5395-1:2013 g.7

Z1-P(X) STAND-ON SERIES SPECIFICATIONS

MODEL	Z1-P 81 CM / 32”	Z1-PX 91 CM / 36”	Z1-PX 122 CM / 48”
Part #	5902230	5902231	5902232
ENGINE			
Make	Kawasaki - Petrol		
Model	FS600V	FX600V	FX730V
Fuel system	Carburetor		
Engine Power	18.5 HP[1] / 13.8 kW @ 3600 rpm	19.0 HP[1] / 14.2 kW @ 3600 rpm	23.5 HP[1] / 17.5 kW @ 3600 rpm
Cylinders / Displacement	2 Cylinders V-Twin / 603 cc	2 Cylinders V-Twin / 603 cc	2 Cylinders V-Twin / 726 cc
Cooling	Air-cooled		
Starting System	Electric		
Fuel Capacity (litres)	23	30	30
MOWER			
Cutting width	81 cm (32”) Triple™	91 cm (36”) Triple™	122 cm (48”) Triple™
Deck Configuration	Configurable deck including: rear discharge, side discharge, mulching and mulching blades		
Cutting Height (cm)	3,8 - 12,7		
Deck Construction	4,6 mm fabricated construction, reinforced spindle mounting area, metal scuff guards, reinforced leading edge		
Mower Spindles	Cast aluminium 133 mm; 25,4 mm shaft		
Deck lift system	Hand-operated, spring assisted		
PTO clutch	Warner MS Clutch-Brake (142 Nm)	Warner MS Clutch-Brake (142 Nm)	Warner MS Clutch-Brake (169Nm)
PTO engagement	Electric		
SUSPENSION & DRIVE TRAIN			
Rear Suspension System	Suspended operator platform utilizing a pivoting platform supported by adjustable rubber isolators for improved operator comfort		
Drive System	Independent Hydro-Gear® ZT-3100® transaxles	Independent Hydro-Gear® ZT-3400® transaxles	Independent Hydro-Gear® ZT-3400® transaxles
Drive Axles	Ø28,6 mm drive shaft with 4-bolt wheel hub		
Drive Tyres (inch)	22 x 7.00 Pneumatic tyre with turf tread	22 x 7.00 Pneumatic tyre with turf tread	22 x 11.00 Pneumatic tyre with turf tread
Caster Tyres (inch)	11 x 4.00 - 5 (4 ply) Flat-free tyre with smooth tread		
GROUND SPEED			
Speed-fwd. (km/h)	0 - 11,2	0 - 12,8	0 - 12,8
Speed-rev. (km/h)	0 - 4,8	0 - 6,4	0 - 6,4
DIMENSIONS			
Overall Length (cm) w/wo rear drop rollers	174 / 170	174 / 170	177,5 / 173,5
Overall width (cm)	87	95	128,5
Overall height (cm)	118	118	118
Dry weight (kg)	342	351	386
OPERATOR CONTROL			
Instrumentation	Fuel gauge, hour meter		
Controls / Safety Circuit	Independent (left and right) forward & reverse levers with stability bar, Automatic PTO Stop, Operator presence in platform, Parking brake safety circuit for starting engine		
Parking Brake	Integrated transaxle brake		
WARRANTY*			
Machine	4-Years Limited Warranty or 750 hours, whichever occurs first. Unlimited hours during the first 2 years.		
Hydro drive belt, tyres, brake pads, hoses, battery, blades	90 Days		
Mower deck drive belt	1-Year or 100 hours, whichever occurs first		
Engine	3-Year Manufacturer’s Limited Warranty		

* See your dealer or www.ferrismowers.eu for warranty details. [1] Power rated by engine manufacturer.









WWW.FERRISMOWERS.EU

Hydro-Gear® is a trademark of Hydro-Gear® Inc. and is used under license
Kawasaki is a registered trademark of Kawasaki Motors Corporation

Kawasaki: All power levels are stated gross horsepower per SAE J1995 / SAE J2723.

Some products shown in this catalogue may not be available in your market.

Please contact your dealer for information on what is available in your country.

We reserve the right to discontinue models, change specifications, features and pricing without notice. No liability can be accepted for printing errors. Product may vary from images shown.

2026© BRIGGS & STRATTON. All rights reserved.

BRIGGS & STRATTON NETHERLANDS BV
Schepersweg 4c, 6049 CV Herten, The Netherlands
Tel. +31 (0)475 40 83 83
info.nl@basco.com

Distributed by:

01/2026EU-EN